

# FELCO 4 - Green

Pruning shear - Good performance - Standard model Made in Switzerland by FELCO




Available from mid 2014











- > Reliable: comfortable, light, sturdy handles made of forged aluminium with a lifetime guarantee\* / blade and riveted anvil blade made of high-quality hardened steel / clean, precise cut / all parts can be replaced
- > Efficient: easy cutting adjustment / wire cutting notch / sap groove
- > Ergonomic: non-slip coating



## **RECOMMENDED FOR**

Our recommendation ( = Recommended, = Strongly recommended, = Best fit)

Viticulture

Arboriculture

Horticulture

Parks and Gardens

Nursery

Small hand

Average-sized hand

Large hand

Right-handed

Left-handed

## THE POINTS OF EXCELLENCE



## Wire cutting notch

The blades feature a notch that allows for the cutting of small wires without damaging the cutting edge.



#### Sap groove

The sap groove prevents the blade sticking when cutting "sappy" wood. It saves time and makes pruning easier by removing sap and debris after each cut.



#### Forged aluminum handles

Lightweight, strong and sturdy thanks to special aluminum alloys and advanced precision forging methods. Equipment comes with a lifetime guarantee\*.



## **ACCESSORIES**









FELCO 902 Sharpening tool Sharpening stone

FELCO 903 Sharpening tool Sharpener

FELCO 910

Holster

Leather - With belt loop and clip

FELCO 910+

Holster

Leather - With belt loop and clip








FELCO 912
Holster
Leather - With belt clip

FELCO 980 Maintenance product Spray

FELCO 990 Maintenance product Grease



# **SPARE PARTS**



FELCO	REF.	Designation	Composition	UCC Barcode
	2/3	Blade	1x 2/3	7 83929 40001 3
	2/3-1	Set	1x 2/3 1x 2/11 1x 2/30	7 83929 40416 5
₩ ***	2/92B	Kit	1x 2/14 + 1x 2/12B + 2x 2/13	7 83929 40392 2
( · · · · · · · · · · · · · · · · · · ·	4/4	Anvil-blade with rivets	1x 4/4 + 4x 2/7	7 83929 40010 5
	4/90	Kit	1x 4/9 + 1x 4/8	7 83929 40015 0
	2/91	Kit	2x 2/11	7 83929 40018 1
	4/1	Handle without blade	1x 4/1 + 3x 2/5B + 1x 2/10 + 1x 2/12 + 1x 2/13 + 1x 2/14 + 1x 4/35	7 83929 40201 7
Co.	4/2	Handle with anvil- blade	1x 4/2 + 1x 4/4 + 4x 2/7 + 1x 4/36	7 83929 40202 4
	4/35	Coating for blade handle	1x 4/35	7 83929 40364 9



-	4/36	Coating for anvil- blade handle	1x 4/36	7 83929 40203 1
=	2/5B	Rivet for blade	1x 2/5B	7 83929 40166 9
-	2/7	Rivet for anvil-blade	1x 2/7	7 83929 40167 6
<b>==)</b>	4/8	Bolt	1x 4/8	7 83929 40204 8
•	4/9	Nut	1x 4/9	7 83929 40205 5
=	2/10	Bush	1x 2/10	7" 83929 40151 5
	2/11	White spring	1x 2/11	7 83929 40152 2
<b>2</b>	2/12	Thumb catch	1x 2/12	7 83929 40153 9
•	2/13	Spring for thumb catch	1x 2/13	7 83929 40154 6
<b>Ç</b> ess	2/14	Screw for thumb catch	1x 2/14	7 83929 40155 3



## **MAINTENANCE**



## Cleaning

It is advisable to clean your tool after each use.

If your tool is particularly dirty or subject to rusting after exposure to moisture, do not delay cleaning.



## Oiling

After cleaning, it is advisable to oil the tool so as to protect it from corrosion. The oil will also unjam the tool.



#### **Sharpening**

It is advisable to sharpen your tool at least once a day, but if you feel that your tool is not cutting as well as usual, sharpen it right away!



## **Dismantling**

It is advisable to dismantle your tool on a regular basis, but at the very latest when it appears to be jammed.



## PARTS REPLACEMENT



#### Changing the blade

When the blade and the anvil-blade no longer cross, or when the blade is badly damaged, it is advisable to change it.

Regulate the working of the blade and anvil-blade by adjusting the tightening of the nut. The blade should rub against the anvil-blade over 2/3 of its length.



#### Changing the thumb catch

When the thumb catch is damaged and loosens when used, even when the screw is readjusted, change it.



## Changing the plastic coatings for handles

If the coatings are badly damaged, you can replace them.

Soak the coatings for 2 minutes in boiling water - recommended glue: Loctite 415.