



REBEL

ACCESS ROPE

CE EN1891-A

DIAMETER

Ø 11 mm

COLOUR OPTIONS

■ WHITE ■ BLUE

■ RED

Also available in full black

LENGTH OPTIONS

60, 70, 100, 200 & 900 meters
Other lengths available on request

TERMINATION

Available with 1 or 2 stitched eyes

Because of the durable, low stretch and flexible hybrid rope construction the Rebel is a great choice for high altitude rope access work. Available in multiple colours and certified for compatibility with all modern mechanical devices on the market. A new standard for efficient ascending, precise work positioning and excellent control when rappelling down.

TECHNICAL SPECIFICATIONS



- Materials / construction: 32-strand Polyester sheath with X-Braid Polyamide core
- Static resistance: 33kN
- Resistance with figure of 8 knot: 23kN
- Mass per meter: 88gram
- Sheath percentage: 41%
- Sheath slippage: 0%
- Elongation 50/150Kg: 2.5%
- Knotability: 1.18
- Retraction with water: 2.2%
- Maximum lifespan: 10 years under normal working conditions

Reference: **ML100+++++**

KEY FEATURES

- Very low stretch
- Superior wear resistance
- Heat treated for extra stability
- Exciting colour combinations
- Retains it's flexibility over time

