



1/2" Rigging Block

20kN WLL | Hot forged aluminum | Working lines up to 1/2" diameter

FEATURES & BENEFITS

- Small sized light weight arborist block accepts working lines up to 1/2" (13mm) diameter
- 20 kN WLL / 100 kN MBS
- Hot forged aluminum side plates with rope friendly rounded cheeks
- Precision CNC machined aluminum sheaves with wide bend radii
- Low profile, secure, easy-to-open captive screw pin lock
- High wall, full diameter, improved anchor sling protection
- Wide, concave upper sheave accepts 5/8" anchor slings
- Flared sideplates reduce twisting in complex rigging scenarios



HOT FORGED ALUMINUM

1.5" LOWER SHEAVE DIA



.75" UPPER SHEAVE DIA

CAPTIVE SCREW PIN LOCK

ITEM #	55352
MSRP	\$159.99
WORKING LOAD LIMIT (WLL)	20 kN (4,496 lbs.)
MBS	100 kN (22,480 lbs.)
MAX WORKING LINE DIAMETER	1/2 in (13mm)
MAX SLING DIAMETER	5/8 in (16mm)
UPPER SHEAVE DIAMETER	.75 in (19mm)
LOWER SHEAVE DIAMETER	1.5 in (38mm)
HEIGHT	4.7 in (118mm)
WIDTH	2.7 in (68mm)
WEIGHT	1 lb. (.45kg)
SIDEPLATE MATERIAL	Aluminum
SHEAVE MATERIAL	Aluminum
AXLE MATERIAL	Stainless Steel
UPC	723466953290
HTS	8483.50.9040
COUNTRY OF ORIGIN	Taiwan



ALUMINUM SHEAVES WITH WIDE BEND RADII

51257	1/2" Rigging Block with 5/8" Ultra Sling	\$229.99
51256	1/2" Rigging Block with 5/8" 2-6' Loopie	\$194.99

09T52021N12B

NotchEquipment.com
Questions? Contact Your Local Sales Rep

