

Guarantee: DMM guarantees this product for 3 years against any defects in materials or manufacture. The guarantee does not cover this product for normal wear through usage, incorrect storage, poor maintenance, accidental damage, negligence, any modifications or alterations, corrosion, or for any usage for which the product was not designed.

The diagram illustrates the correct and incorrect use of a rope grab on a rope. On the left, a checkmark indicates the correct application: a rope grab is attached to a single rope, and the text "MAX 2kN" is shown with two upward arrows. On the right, a skull and crossbones indicates the incorrect application: a rope grab is attached to a rope that is part of a braid or complex structure, and the text "MAX 2kN" is shown with a single arrow pointing to the rope.

F302A/QA/33/Jan.2016



DDM
LLANBERIS, GWYNEDD,
UNITED KINGDOM,
LL55 4EL.
Tel: +44 (0) 1286 872 222
Fax: +44 (0) 1286 872 090
e-mail: post@ddmmwales.com
web: www.ddmmwales.com



Sewn Tape Slings, Sewn Tape Lanyards & Rope Lanyards

**EN566:2006, EN354:2010,
EN795(b):2012 & UIAA104:2009**

0120 €

EN, FR, DE, IT, ES, PT, NL

The diagram illustrates the effect of different knot configurations on the load capacity of a rope and carabiner system. The configurations and their corresponding load capacities are as follows:

Knot Configuration	Load Capacity
Simple rope and carabiner (no knot)	100%
Two parallel ropes with carabiners	200%
Figure-eight knot	~ 50%
Overhand knot	~ 50%
Reef knot (square knot)	~ 50%

NO, SV, FI, DK, PL, CZ, SK

